R 68 HO

IP 44 | LED 24

Flat, High-output LED recessed light for a 68 mm cut-out R 68-LED HO 4W nw stainless-steel look





Description:
LED-Recessed spotlight, Plastic housing, Connection cable 2,5 m with LED 24 plug, light colour neutral white approx. 4000 K, Quick and easy installation using Snap hooks, optional accessories: dimmable Transformer with Wireless remote control or 1-10 V Dimmer, Screw-on mounting spring for secure support in lightweight ceilings, Mounting ring for installation without a recessed hole.

Connection: LED-Trafo DC 24V
Light colour: 4000K Neutral white
Beam angle: 110°
Energy efficiency: LED: 113 lm/W; Leuchte: 300 lm/m (75 lm/W)
Energy efficiency class: N/A
Symbols: IP44, SK III
Weight: 0,08 kg

Special features:

- Flush installation in 16 mm panels
- Light colour: 4000 K neutral white
- Connection cable 2,5 m with LED 24 plug
- Design: Wide-beam spotlight >80°
- LED Transformer DC 24 V
- Connector system: LED 24
- Protection rating: IP44 [with Blind hole]
- Dimmable with compatible control
- Housing colour: Stainless-steel look

R 68 HO



	110°	Ø	ww	nw
0,5m		620	532 lx	532 lx
1,0m		1240	133 lx	133 lx
1,5m		1860	59 lx	59 lx
2,0m		2480	33 lx	33 lx
2,5m		3100	21 lx	21 lx

Drilling hole



68mm



Order number:
61001261308

limited availability

HERA LED WARRANTY 5 YEARS

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	Gehäusefarbe	light colour
61001261308	R 68-LED HO 4W nw stainless-steel look	Stainless-steel look	4000K Neutral white
61054913802	3er Set R 68-LED HO 4W ww stainless-steel look	Stainless-steel look	3000K Warm white
61054915802	5er Set R 68-LED HO 4W ww stainless-steel look	Stainless-steel look	3000K Warm white
61054913803	3er Set R 68-LED HO 4W nw stainless-steel look	Stainless-steel look	4000K Neutral white

Order number: 61001261308

