# Dynamic Tape

CE | MM | IP20 | SK III | Dynamic | configurator

Self-adhesive, with adjustable colour appearance Dynamic LED Tape 5m 2x600 LED 72W

Description:

Flexible LED tape on roll with adjustable light color, light color adjustable between 2700K and 5000K, quick and easy installation by the already applied double-sided 3M tape, supply cable 2,5m already attached, the tape can be cut every 50mm (see marking). Then the tape can be contacted again without soldering with the connection clip or the cables, optional accessories: glass edge profile for lateral light supply of glass panes, corner profile, cover profiles, milled profiles or mounting profiles, controller with radio remote control DALI, ZigBee or WiFi app

| **Connection:**	LED-Trafo DC 24 V
Life:	L70/B10 >= 50.000 h
Light colour:	2700 – 5000 K (Dynamic) adjustable
Beam angle:	120°
Energy efficiency:	LED: 129 lm/W; luminaire: 1470 lm/m (100 lm/W)
Energy efficiency class:	F
Colour rendering:	Ra/CRI >= 80
Symbols:	CE, MM, IP20, SK III
EAN-No.:	4051268129442
Weight:	0,12 kg

Special features:

- max. 5m on one supply cable
- quick and easy installation due to double-sided adhesive tape
- tapes can be shortened at 50mm intervals (marking underneath the adhesive foil)
- the power (W) of partial sections cannot be calculated linearly, please refer to the configurator!
- colour appearance between 2700K (xw) and 5000K (cw) adjustable

Dynamic Tape

120°		Ø	xw	nw	cw
0,5m		650	2672 lx	2848 lx	3008 lx
1,0m		1300	668 lx	712 lx	752 lx
1,5m		1950	297 lx	316 lx	334 lx
2,0m		2600	167 lx	178 lx	188 lx
2,5m		3250	107 lx	114 lx	120 lx

connecting clip | connecting cable | supply cable

Order number:
20202601301

article in stock

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description
20202601301	Dynamic LED Tape 5m 2x600 LED 72W

supply cable

2500
14
5
5

connecting cable

16
50
5
14,2

connecting clip

30

5000
3
8,3
50
10