

Basic-Tape S



Self-adhesive, silicone coated, ingress protection IP54 LED Basic-Tape S 5m 600 LED 40W xw



Description:

Flexible LED tape with silicon protection on roll, colour appearance extra warm white 2700K, quick and easy installation due to 3M double-sided adhesive tape, supply cable 2,5m already attached, the tape can be shortened at 50mm (see marking). optional accessories: glass edge profile for lateral light supply of glass panes, corner profiles, cover profiles, milled profiles or mounting profiles, controller with radio remote control DALI, ZigBee or WiFi app


Connection: LED-Trafo DC 24V
Life: L70/B10 >= 40.000h
Light colour: 2700K extra warm white
Beam angle: 120°
Energy efficiency: LED: 129 lm/W; luminaire: 780 lm/m (98 lm/W)
Energy efficiency class: F
Colour rendering: Ra/CRI >= 85
Symbols: CE, MM, IP54, SK III
EAN-No.: 4,05E+12
Weight: 0,22 kg

Special features:

- max. 6m per supply cable
- quick and easy installation due to double-sided adhesive tape
- tapes can be shortened at 50mm intervals according to the marks on the front side)
- after removing the silicone layer from the connection pad the strips can be connected with the clips and connecting cables (now IP20 only)
- the power (W) of partial sections cannot be calculated linearly, please refer to the configurator!
- with IP54, suitable for applications requiring higher ingress protection (general humidity, bathroom, kitchen, shops). The silicone compound assures an additional mechanical protection e.g. for frequent cleaning work.

Basic-Tape S

	120°	Ø	xw	ww	nw
0,5m		610	884 lx	952 lx	1024 lx
1,0m		1220	221 lx	238 lx	256 lx
1,5m		1830	98 lx	106 lx	114 lx
2,0m		2440	55 lx	60 lx	64 lx
2,5m		3050	35 lx	38 lx	41 lx



Order number:
20202630234

article in stock

available versions

Choose from the options below. The currently selected one is highlighted in color.

[illegible]

[illegible]

