

Power-Stick S



Powerful, pluggable linear luminaire 24V DC LED Power-Stick S 200mm 6 LED 2,7W xw



Description:

Plug-in LED stick without dark zones in aluminium profile, colour appearance `xw` approx.2700K, easy mounting by enclosed clips, supply cable easy to attach and up to 2,4m of sticks or one stick SE (with side-connection) for continuous strip lighting, optional accessory: dimmable transformer with radio telecontrol or 1-10V Dimmer, push switch, cover and milled profile for complete recessing in wood


Connection: 220 - 240V / 50 - 60Hz
Life: L70/B10 >= 40.000 h
Light colour: 2700 K extra warm white
Beam angle: 120°
Energy efficiency: LED 113 lm/W; luminaire: 935 lm/m (70 lm/W)
Energy efficiency class: G
Colour rendering: Ra/CRI >= 95
Symbols: CE, MM, IP20, SK III
EAN-No.: 4051268108027
Weight: 0,025 kg

Special features:

- max. 32 W or 2,4 m per supply cable
- without dark zones
- LED Stick with lateral feeder for continuous strip lighting

Power-Stick S

	120°	Ø	xw	ww	nw
0,5m		610	1660 lx	1700 lx	1800 lx
1,0m		1220	415 lx	425 lx	450 lx
1,5m		1830	184 lx	189 lx	200 lx
2,0m		2440	104 lx	106 lx	113 lx
2,5m		3050	66 lx	68 lx	72 lx



Order number:
20202410104

article in stock

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	light colour
20202410104	LED Power-Stick S 200mm 6 LED 2,7W xw	2700 K extra warm white
20202410204	LED Power-Stick S 300mm 12 LED 4,0W xw	2700 K extra warm white
20202411204	LED Power-Stick S 300mm 12 LED 4,0W xw SE 2,5m	2700 K extra warm white
20202410102	LED Power-Stick S 200mm 6 LED 2,7W ww	3000 K warm white
20202410202	LED Power-Stick S 300mm 12 LED 4,0W ww	3000 K warm white
20202411202	LED Power-Stick S 300mm 12 LED 4,0W ww SE 2,5m	3000 K warm white
20202410103	LED Power-Stick S 200mm 6 LED 2,7W nw	4000 K neutral white
20202410203	LED Power-Stick S 300mm 12 LED 4,0W nw	4000 K neutral white
20202411203	LED Power-Stick S 300mm 12 LED 4,0W nw SE 2,5m	4000 K neutral white

