


Dim-2-Warm SR 68















Description:

Swiveling recessed LED spotlight, metal housing, connecting cable 0.2m with LED 350 plug, light color ww (warm white) approx. 3000K is getting warmer (up to 2000K) while dimming (trailing edge dimmer only), quick and easy installation by spring clips, accessories: small round phase dimmable transformer for 68mm bore hole

Connection: LED-Trafo DC 350 mA
Life: L70/B10 >= 35.000 h
Light colour: 3000 K warm white

Beam angle: 43°

Energy efficiency: LED: 93 lm/W; luminaire: 455 lm (70 lm/W)

Energy efficiency class: G


Colour rendering: Ra/CRI >= 90

Symbols: CE, MM, IP44, UGR<19, SK III


EAN-No.: 4051268194235 **Weight:** 0,12 kg

Special features:

- swivels and tilts 20° to both sides
- metal casing
- colour appearance ww (warm white) approx. 3000 K is getting warmer (up to 2000 K) while dimming (trailing edge dimmer only)
- suitable for screen workplaces! (UGR < 19)








Order number: 20203010201

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	colour of housing
20203010201	Dim-2-Warm SR 68 6,5W ww white	white
20203010206	Dim-2-Warm SR 68 6,5W ww matt chrome	matt chrome
20203010208	Dim-2-Warm SR 68 6,5W ww stainless steel look	stainless steel





Order number: 20203010201

