FR 78

Flat recessed luminaire FR 78-LED 4W ww matt chrome

CE · UL · IP44 · LED 24


Foto: Juwelier Hohage

Description:

LED recessed spotlight with planar light, plastic housing, connecting cable 2.5m with LED 24-plug, light color warm white approx. 3000K, quick and easy installation with snap-in hooks, optional accessories: dim controller with remote control, DALI or 1-10V dimmer, mounting spring for a secure hold in lightweight ceilings, surface-mounting ring for installation without mounting hole

Connection:	LED-Trafo DC 24 V
Life:	L70/B10 >= 50.000 h
Light colour:	3000 K warm white
Beam angle:	110°
Energy efficiency:	LED: 113 lm/W; luminaire: 270 lm (68 lm/W)
Energy efficiency class:	G
Colour rendering:	Ra/CRI >= 93
Symbols:	CE, MM, UL, IP44, SK III
EAN-No.:	4051268127691
Weight:	0,07 kg

Special features:

- flush mounting in 16 mm panels
- no visible luminous spots

FR-/FQ 68/78

	Ø	xw	ww	nw
0,5m	620	416 lx	440 lx	440 lx
1,0m	1240	104 lx	110 lx	110 lx
1,5m	1860	46 lx	49 lx	49 lx
2,0m	2480	26 lx	28 lx	28 lx
2,5m	3100	17 lx	18 lx	18 lx

Drilling hole

78mm

Order number:
61001760206

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	colour of housing	light colour
61001760206	FR 78-LED 4W ww matt chrome	matt chrome	3000 K warm white
61001760208	FR 78-LED 4W ww stainless steel look	stainless steel	3000 K warm white
61001760306	FR 78-LED 4W nw matt chrome	matt chrome	4000 K neutral white
61001760308	FR 78-LED 4W nw stainless steel look	stainless steel	4000 K neutral white
61056838002	set of 3 FR 78-LED 4W ww stainless steel look	stainless steel	3000 K warm white
61056838003	set of 3 FR 78-LED 4W nw stainless steel look	stainless steel	4000 K neutral white
61056858002	set of 5 FR 78-LED 4W ww stainless steel look	stainless steel	3000 K warm white
61056858003	set of 5 FR 78-LED 4W nw stainless steel look	stainless steel	4000 K neutral white

Order number: 61001760206

use spacer min. 50 mm at insulation

1,5

1,5

min. 12

max. 16

200

26

with mounting spring

14

13,5

71

74

Ø 75

1,5

12

1,3

13

73

12

Ø 75

12

1,3

Ø 82

FR 68-LED

FQ 68-LED

FR 78-LED