

Q 68 HO

Flat recessed luminaire square Q 68-LED HO 4W nw stainless steel



Description:

Square recessed LED spotlight for 68mm bore, plastic housing, connecting cable 2.5m with LED 24-plug, light color neutral white approx. 4000K, quick and easy installation with snap-in hooks, optional accessories: dimmable transformer with remote control or 1-10V dimmer, mounting spring for a secure hold in lightweight ceilings, surface-mounting ring for installation without mounting hole


Connection: LED-Trafo DC 24V
Life: L70/B10 >= 40.000h
Light colour: 4000K neutral white
Beam angle: 110°
Energy efficiency: LED: 113 lm/W; luminaire: 300 lm (75 lm/W)
Energy efficiency class: G
Colour rendering: Ra/CRI >= 93
Symbols: CE, MM, UL, IP44, SK III
EAN-No.: 4,05E+12
Weight: 0,08 kg

Special features:

- flush mounting in 16mm panels

R 68 HO / Q 68 HO


	110°	Ø	ww	nw
0,5m		620	532 lx	532 lx
1,0m		1240	133 lx	133 lx
1,5m		1860	59 lx	59 lx
2,0m		2480	33 lx	33 lx
2,5m		3100	21 lx	21 lx



Drilling hole



68mm



Order number:
61001263308

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description
61001263308	Q 68-LED HO 4W nw stainless steel

