

Zubehör Linienleuchten



Light control for colour temperature 24V Dynamic-Controller WiFi / Alexa 75W with 12-way distributor 2)



Description:

WiFi controller for switching and controlling 24V dynamic luminaires, easy plug-in connection for new or existing installations, controllable with every iOS or Android smartphone or tablet (Hera-App for free), with memory function (after cut off from mains the last colour and brightness setting is recovered), supply cable with two LED 24-plugs and 12-way distributor for the luminaires

Connection: LED-Trafo DC 24V

Symbols: CE, MM, IP20, SK III

EAN-No.: 4,05E+12

Weight: 0,1 kg

Special features:

Connection: 24V DC / for Dynamic luminaires with Dynamic plug
Other:

- easy plug-in connection for new or existing installations
- with memory function (after disconnection from the mains, the previous dimming status is restored)
- Radio remote controls for dimming, switching and colour setting
- flush-mounted touch remote control for dimming, switching and colour setting with customary push button (operating distance 15m / less for walls and ceilings)
- 4 channel remote control with master button and wall mounting combinable with dim controllers
- surface mounted remote control with wall mounting
- recessed remote control for wood with 35mm cut-out, depth min. 12mm incl. mounting housing stainless steel look or for use in standard sockets
- multiple radio controllers can be activated simultaneously using one remote control
- all controllers with „Soft Off“ and „Multicontrol“ (it is possible to program up to 7 remote controls to one controller)
- DALI controller
- for connection to complex controls or bus systems
- BLE Controller (Bluetooth Low Energy)
- controllable via any iOS or Android smartphone or tablet (with free Meshle app)
- Indoor range up to 15m (Mesh network)
- freely programmable scenes
- very easy installation due to plug & play components and plug-in systems
- can be used individually as a stand-alone control
- up to 30 controllers automatically connect to each other and can be controlled via Bluetooth in the app
- incl. timer function (individual switch-on and switch-off times)

Order number:
61500050922

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	safety class	connection system	protection class	connection
21304108107	Stirndeckel LED Montageprofil Twin Stick	-	-	-	-
20204090004	Federblech LED Twin-Stick	-	-	-	-
61500050922	24V Dynamic-Controller WiFi / Alexa 75W with 12-way distributor 2)	IP20	Dynamic	SK3	LED-Trafo DC 24V