


Wall



230V flush-mounted wall recessed luminaire for 68mm hole Wall F 0,9W white RAL 9016



Description:

LED wall recessed luminaire, easy installation in standard surface pattress box and flush-mounted socket, direct connection to 230V, no visible luminous spot

Connection: 220 - 240V / 50 - 60Hz
Life: L70/B10 >= 60.000h
Light colour: 3000K warm white
Beam angle: 120°
Energy efficiency: LED: 105 lm/W luminaire: 50 lm (55 lm/W)
Energy efficiency class: G
Colour rendering: Ra/CRI >= 84
Symbols: CE, MM, ENEC18, IP20, SK I
EAN-No.: 4,05E+12
Weight: 0,065 kg


Special features:

- quick and easy installation due to standard surface pattress box and flush-mounted socket
- direct connection to 230V
- no visible luminous spots
- decorative rings also available individually NEW: versions "I" with integrated invisible motion detector (run-on time: 3 min.)

Drilling hole



68mm



Order number:
20202720201

article in stock

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	colour of housing	energy efficiency
20202720201	Wall F 0,9W white RAL 9016	White	LED: 105 lm/W luminaire: 50 lm (55 lm/W)
20202720208	Wall F 0,9W stainless steel	Stainless steel	LED: 105 lm/W luminaire: 50 lm (55 lm/W)
20202720101	Wall F 1,8W white RAL 9016	White	LED: 105 lm/W luminaire: 90 lm (50 lm/W)
20202720108	Wall F 1,8W stainless steel	Stainless steel	LED: 105 lm/W luminaire: 90 lm (50 lm/W)
20202721101	Wall Up & Down 1,8W white RAL 9016	White	LED: 105 lm/W luminaire: 90 lm (50 lm/W)
20202722101	Wall Down 1,8W white RAL 9016	White	LED: 105 lm/W luminaire: 90 lm (50 lm/W)
20202722108	Wall Down 1,8W stainless steel	Stainless steel	LED: 105 lm/W luminaire: 90 lm (50 lm/W)
20202720401	Wall IF 1,8W white RAL 9016	White	LED: 105 lm/W luminaire: 90 lm (50 lm/W)
20202720408	Wall IF 1,8W stainless steel	Stainless steel	LED: 105 lm/W luminaire: 90 lm (50 lm/W)
20202721201	Wall I Up & Down 1,8W white RAL 9016	White	LED: 105 lm/W luminaire: 90 lm (50 lm/W)
20202721208	Wall I Up & Down 1,8W stainless steel	Stainless steel	LED: 105 lm/W luminaire: 90 lm (50 lm/W)

