

ECO R 68



recessed light with 2 Leistungen and 4 Lichtfarben for 230 V Eco R 68 module 5/8W xw/ww/nw/xc



Description:

Dimmable LED-Recessed spotlight, incl. Connection terminal for 230 V with integrated through-wiring, Quick and easy installation using Spring terminals, Light colour and Power on the Spotlight umschaltbar. Light colour: 3000 / 4000 K Umschaltbar.

Connection: 220 - 240V / 50 - 60Hz
Light colour: 3000 / 4000K Adjustable
Beam angle: 60°
Energy efficiency: Leuchte: 565 - 880 lm/m (111- 116 lm/W)
Symbols: IP65, SK II
Weight: 0,22 kg

Special features:

- Two Leistungsstufen on the Spotlight umschaltbar
- Four Light colours on the Spotlight umschaltbar
- Direct connection to 230 V with integrated through-wiring or Wieland/Adels-Plug
- Dank IP65 ideal suitable for Anwendungen with erhöhter Protection rating (general Moisture, z.B. Bathroom- and Kitchen area)
- Recommended Phases-Dimmer: Busch-Jaeger 6523U-102, Jung 1731DD or 1711DE or GIRA 117600/I03
- Power 5 W or. 8 W on the Transformer umschaltbar
- Light colour: 3000 / 4000 K Umschaltbar
- Incl. Connection terminal for 230 V with integrated through-wiring
- Design: Flexible LED strip
- 220-240 V / 50-60 Hz
- Protection rating: IP65


Eco R 68 8W

60°	Ø	xw	ww	nw	xc
0,5m	577	3844 lx	4140 lx	4352 lx	4056 lx
1,0m	1155	961 lx	1035 lx	1088 lx	1014 lx
1,5m	1732	427 lx	460 lx	484 lx	451 lx
2,0m	2309	240 lx	259 lx	272 lx	254 lx
2,5m	2887	154 lx	166 lx	174 lx	162 lx

Drilling hole



68-80 mm



Order number:
20807081001

article in stock



available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description
20807081001	Eco R 68 module 5/8W xw/ww/nw/xc

