

SR 45-24V



Flat, Swivelling LED recessed light SR 45-24V 5,8W ww white



Description:

Pivotable LED-Recessed spotlight, Metal housing, Connection cable 2,5 m with LED 24 plug, Quick and easy installation using Spring terminals, optional accessories: dimmable Transformer for Phase-cut dimmer, Dimmcontroller 1-10 V, DALI, CASAMBI, BLE, ZigBee or Wireless-Remote controls, light colour warm white approx. 3000 K, pivotable in two Directions by per 20°.

Connection: LED-Trafo DC 24V

Light colour: 3000K Warm white

Beam angle: 44°

Energy efficiency: LED: 138 lm/W; Leuchte: 650 lm/m (112 lm/W)

Symbols: IP44, SK III

Weight: 0,08 kg

Special features:

- On both sides pivotable by 20°
- Metal housing
- Light colour: 3000 K warm white
- Connection cable 2,5 m with LED 24 plug
- Design: Spot 760°
- LED Transformer DC 24 V
- Connector system: LED 24
- Protection rating: IP44
- Dimmable with compatible control
- Adjustable version
- Housing colour: White

SR 45-24V

40°	Ø	ww	nw
0,5m	364	4580 lx	4924 lx
1,0m	728	1145 lx	1231 lx
1,5m	1092	509 lx	547 lx
2,0m	1456	286 lx	308 lx
2,5m	1820	183 lx	197 lx

Drilling hole



45mm

Order number:
20202572102

limited availability



available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description
20202572102	SR 45-24V 5,8W ww white
20202572802	SR 45-24V 5,8W ww stainless-steel look
20202572103	SR 45-24V 5,8W nw white
20202572803	SR 45-24V 5,8W nw stainless-steel look