SR 68 5.8W

IP 44 | LED 24

Swivelling recessed ceiling spotlight for 68–80 mm ceiling cut-outs SR 68-24V 5,8W 25° ww matt chrome




Description:
SR 68-24 V 5,8 W 25° ww matt chrome for a targeted, high-quality Furniture- and Object lighting. Version: LED Transformer DC 24 V, Connector system LED 24, IP44. Light colour: 2700 K extra warm white. Suitable for display screen workstations! (UGR<19). Connection cable 2,5 m with LED 24 plug.

Connection:	LED-Trafo DC 24V
Light colour:	2700K Extra warm white
Beam angle:	25°
Energy efficiency:	LED: 138 lm/W; Leuchte: 650 lm/m (112 lm/W)
Energy efficiency class:	E
Symbols:	IP44, SK III
Weight:	0,15 kg

Special features:

- Gimbal-mounted pivotable by 20°
- Metal housing
- Suitable for display screen workstations! (UGR<19)
- Light colour: 2700 K extra warm white
- Connection cable 2,5 m with LED 24 plug
- Beam angle 25° or 40°
- Design: Spot ?60°
- LED Transformer DC 24 V
- Connector system: LED 24
- Protection rating: IP44
- Dimmable with compatible control
- Adjustable version
- Housing colour: Matt chrome

SR 68-24V 5,8W



38°	Ø	xw	ww	nw
0,5m	344	3992 lx	4516 lx	4827 lx
1,0m	689 998 lx	1129 lx	1207 lx	
1,5m	1033	444 lx	502 lx	536 lx
2,0m	1377	250 lx	282 lx	302 lx
2,5m	1722	160 lx	181 lx	193 lx

Drilling hole



68-74mm (ohne Ring) 68-84mm (mit Ring)

Order number:
20202404602

limited availability



available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	Gehäusefarbe	shielding angle
20202404602	SR 68-24V 5,8W 25° ww matt chrome	Chrom-matt	25°
20202404603	SR 68-24V 5,8W 25° nw matt chrome	Chrom-matt	25°
20202405104	SR 68-24V 5,8W 40° xw white	Anodized aluminum	40°
20202405304	SR 68-24V 5,8W 40° xw black	Black	40°
20202405604	SR 68-24V 5,8W 40° xw matt chrome	Chrom-matt	40°
20202405804	SR 68-24V 5,8W 40° xw stainless-steel look	Stainless-steel look	40°
20202405102	SR 68-24V 5,8W 40° ww white	Anodized aluminum	40°
20202405302	SR 68-24V 5,8W 40° ww black	Black	40°
20202405602	SR 68-24V 5,8W 40° ww matt chrome	Chrom-matt	40°
20202405802	SR 68-24V 5,8W 40° ww stainless-steel look	Stainless-steel look	40°
20202405103	SR 68-24V 5,8W 40° nw white	Anodized aluminum	40°
20202405603	SR 68-24V 5,8W 40° nw matt chrome	Chrom-matt	40°
20202405803	SR 68-24V 5,8W 40° nw stainless-steel look	Stainless-steel look	40°