Dynamic FR 55

LED recessed light with area lighting and adjustable light colour Dynamic FR 55-LED 3W black





Description:
LED-Recessed spotlight with Area light, Plastic housing, Connection cable 2,5 m with Dynamic plug, Light colour adjustable between approx. 2700 K and 5000 K, Quick and easy installation using Snap hooks, optional accessories: Mounting ring for installation without a recessed hole, Control via Wireless-Remote control or WiFi-Controller.

Connection:	LED-Trafo DC 24V
Light colour:	2700 - 5000K (Dynamic) adjustable
Beam angle:	110°
Energy efficiency:	LED: 113 lm/W; Leuchte: 210 lm/m (70 lm/W)
Energy efficiency class:	G
Symbols:	IP44, SK III
Weight:	0,07 kg

Special features:

- Also for Sheet-metal installation suitable
- No visible points of light
- Light colour: 2700 - 5000 K (Dynamic) adjustable
- Connection cable 2,5 m with Dynamic plug
- Design: Wide-beam spotlight >80°
- LED Transformer DC 24 V
- Connector system: Dynamic
- Protection rating: IP44 [with Blind hole]
- Dimmable with compatible control
- Housing colour: Black

Dynamic FR 55



	Ø	ww	nw	cw
0,5m	1428	312 lx	328 lx	344 lx
1,0m	2856	78 lx	82 lx	86 lx
1,5m	4284	35 lx	36 lx	38 lx
2,0m	5713	20 lx	21 lx	22 lx
2,5m	7141	12 lx	13 lx	14 lx

Drilling hole



55-58mm



Order number:
61001790103

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	Gehäusefarbe
61001790103	Dynamic FR 55-LED 3W black	Black
61001790106	Dynamic FR 55-LED 3W matt chrome	Chrom-matt
61001790108	Dynamic FR 55-LED 3W stainless-steel look	Stainless-steel look
61057830108	3er Set Dynamic FR 55-LED 3W stainless-steel look	Stainless-steel look

Order number: 61001790103

