Dynamic FR 78

LED recessed light with area lighting and adjustable light colour Dynamic FR 78-LED 4W stainless-steel look





Description:
LED-Recessed spotlight with Area light, Plastic housing, Connection cable 2,5 m with Dynamic plug, Light colour adjustable between approx. 2700 K and 5000 K, Quick and easy installation using Snap hooks, optional accessories: Screw-on mounting spring for secure support in lightweight ceilings, Mounting ring for installation without a recessed hole, Control via Wireless-Remote control or WiFi-Controller.

Connection:	LED-Trafo DC 24V
Light colour:	2700 - 5000K (Dynamic) adjustable
Beam angle:	110°
Energy efficiency:	LED: 113 lm/W; Leuchte: 270 lm/m (68 lm/W)
Energy efficiency class:	N/A
Symbols:	IP44, SK III
Weight:	0,07 kg

Special features:

- Flush installation in 16 mm panels
- No visible points of light
- Light colour: 2700 - 5000 K (Dynamic) adjustable
- Connection cable 2,5 m with Dynamic plug
- Design: Area-light module / Hinterleuchtungsmodul
- LED Transformer DC 24 V
- Connector system: Dynamic
- Protection rating: IP44 [with Blind hole]
- Dimmable with compatible control
- Housing colour: Stainless-steel look

Dynamic FR 78



	Ø	ww	nw	cw
0,5m	620	372 lx	400 lx	444 lx
1,0m	1240	93 lx	100 lx	111 lx
1,5m	1860	41 lx	44 lx	49 lx
2,0m	2480	23 lx	25 lx	28 lx
2,5m	3100	15 lx	16 lx	18 lx

Drilling hole



78mm





Order number:
61001770108

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	Gehäusefarbe
61001770108	Dynamic FR 78-LED 4W stainless-steel look	Stainless-steel look
61057730108	3er Set Dynamic FR 78-LED 4W stainless-steel look	Stainless-steel look

Order number: 61001770108

