

Dynamic FAR 68



LED recessed light with area lighting and adjustable light colour Dynamic FAR 68-LED 3W stainless-steel look



Description:

LED-Recessed spotlight with Area light, Housing Metal, Connection cable 2,5 m with Dynamic plug on the Spotlight pluggable, Light colour adjustable between approx. 2700 K and 5000 K, Quick and easy installation using Snap hooks, optional accessories: Screw-on mounting spring for secure support in lightweight ceilings, Control with Wireless remote control, Alexa, WiFi, DALI, ZigBee or Casambi Controller.

Connection: LED-Trafo DC 24V

Light colour: 2700 - 5000K (Dynamic) adjustable

Beam angle: 105°

Energy efficiency: LED: 120 lm/W; Leuchte: 225 lm/m (75 lm/W)

Symbols: IP44, SK III

Weight: 0,08 kg

Special features:

- o Metal housing
- o Flush installation in 16 mm panels
- o No visible points of light
- o Light colour: 2700 - 5000 K (Dynamic) adjustable
- o Connection cable pluggable 2,5 m with Dynamic plug
- o Design: Wide-beam spotlight >80°
- o LED Transformer DC 24 V
- o Connector system: Dynamic
- o Protection rating: IP44 [with Blind hole]
- o Dimmable with compatible control
- o Housing colour: Stainless-steel look


Dynamic FAR 68

	105°	Ø	xw	nw	cw
0,5m		1303	372 lx	352 lx	364 lx
1,0m		2606	93 lx	88 lx	91 lx
1,5m		3910	41 lx	39 lx	40 lx
2,0m		5213	23 lx	22 lx	23 lx
2,5m		6516	15 lx	14 lx	15 lx

Drilling hole



68mm



Order number:
20203190008

article in stock



available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description
20203190003	Dynamic FAR 68-LED 3W black
20203190008	Dynamic FAR 68-LED 3W stainless-steel look

