
Dynamic FAQ 68

LED recessed light with area lighting and adjustable light colour Dynamic FAQ 68-LED 3W black






Description:
LED-Recessed spotlight with Area light, Housing Metal, Connection cable 2,5 m with Dynamic plug on the Spotlight pluggable, Light colour adjustable between approx. 2700 K and 5000 K, Quick and easy installation using Snap hooks, optional accessories: Screw-on mounting spring for secure support in lightweight ceilings, Control with Wireless remote control, Alexa, WiFi, DALI, ZigBee or Casambi Controller.

Connection:	LED-Trafo DC 24V
Light colour:	2700 - 5000K (Dynamic) adjustable
Beam angle:	115°
Energy efficiency:	LED: 120 lm/W; Leuchte: 225 lm/m (75 lm/W)
Energy efficiency class:	G
Symbols:	IP44, SK III
Weight:	0,1 kg

Special features:

- Metal housing
- Flush installation in 16 mm panels
- No visible points of light
- Light colour: 2700 - 5000 K (Dynamic) adjustable
- Connection cable pluggable 2,5 m with Dynamic plug
- Design: Wide-beam spotlight >80°
- LED Transformer DC 24 V
- Connector system: Dynamic
- Protection rating: IP44 [with Blind hole]
- Dimmable with compatible control
- Housing colour: Black

Dynamic FAQ 68





	Ø	xw	nw	cw
0,5m	1570	336 lx	352 lx	364 lx
1,0m	3139	84 lx	88 lx	91 lx
1,5m	4709	37 lx	39 lx	40 lx
2,0m	6279	21 lx	22 lx	23 lx
2,5m	7848	13 lx	14 lx	15 lx

Drilling hole



68mm





Order number:
20203195003

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	Gehäusefarbe
20203195003	Dynamic FAQ 68-LED 3W black	Black
20203195008	Dynamic FAQ 68-LED 3W stainless-steel look	Stainless-steel look

Order number: 20203195003

