Surface-mounted wireless remote control - Dimm

IP 20

Dimming controller as an optional accessory for 24V transformers Surface mounted remote control dim black



Description:
Surface mounting-Wireless remote control as Extension for Pair on already existing Wireless controller Dimm, incl. Battery. With memory function (the previous brightness is restored after disconnection from the mains). With a Remote control or. per Channel can any number of many Wireless controller in parallel controlled are.

Order number:
61500050603

article in stock

HERA LED WARRANTY 5 YEARS

Connection:	N/A
Light colour:	N/A
Energy efficiency class:	N/A
Symbols:	IP20
Weight:	0,05 kg

Special features:

- As Extension to a existing Controller
- All Controller with „Soft Off“ and „Multicontrol“ (it can Up to 7 various Transmitter on a Controller paired are)
- The Transmitter can in each case in parallel on any number of many Controller paired are
- 24 V DC
- Ready to plug in and suitable as an option for every new installation or subsequent extension of the existing system
- With memory function (the previous brightness is restored after disconnection from the mains)
- Wireless remote controls for Dim and Switch
- Surface mounting-Wireless remote control with Wall bracket
- With a Remote control or. per Channel can any number of many Wireless controller in parallel controlled are
- DALI Controller
- For connection to complex control systems and bus systems
- BLE Controller (Bluetooth Low Energy)
- Controllable via any iOS or Android Smartphone or Tablet (with free Meshle-App)
- Range Indoor area Up to 15 m (Mesh-Network)
- Freely programmable scenes
- Extremely easy Installation using Plug & Play Components and Connector systems
- Can be used individually as a stand-alone control
- Up to 30 Controller connect automatically with one another and can via Bluetooth in the App controlled are
- Incl. Timer-Function (individual A- and Switch-off times)
- For Lights with LED 24 plug
- Sonar Controller for unsichtbaren Switch and Dim hinter Wood, Glass, Stein or Keramik of max. 40 mm Stärke

- UP Wireless-Push-button-Module for Dim and Switch with commercially available Push-button (Range 15 m / with Walls and Ceilings low)
- 4 Channel-Wireless remote control incl. Master-Push-button and Wall bracket, also can be combined with Dynamic-Controllers
- Recessed installation-Wireless remote control for Wood drill hole ø 35 mm min. 12 mm deep incl. Surface-mounted housing in stainless-steel look or for the Use in Standard-Socket outlets
- Housing colour: Black

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	Gehäusefarbe
61500050603	Surface mounted remote control dim black	Black
61500050601	Anbau-wireless remote control Dimm stainless steel	Stainless-steel look