IR switch 230V

IP 20

Contactless switch with different sensor heads IR-S with K 59 sensor AE



Description:
Touchless IR-Switch for 220–240 V / 50–60 Hz for connecting Lights-Control gear the Protection class II. The Approach to the Sensor head K 59 releases the Switching circuit made of. The The first movement switches the light on, the following Movement switches it made of. The The memory function restores the previous switching state after disconnection from the mains. The Mains connection cable is 2 m and the Switching cable 0,3 m long. Beide Cables are stripped and with Wire-end ferrules for Connection to Screw- or Plug-in terminals versehen. The Sensor cable with Sensor head K 59 is 3 m long. Suitable For switching LED Transformers up to 250 W or SlimLite®-Lines of light with Up to 3 Lights. Depending on the surface, the distance between the sensor and the inside of the door should be 4 to 50 mm amount to.

Order number:
50612060112

limited availability

HERA LED WARRANTY 5 YEARS

Connection:	220 - 240V / 50 - 60Hz
Light colour:	N/A
Energy efficiency class:	N/A
Symbols:	IP20, SK II
Weight:	0,19 kg

Special features:

- Touchless IR switch for 230 V
- Approaching the sensor triggers the switching operation
- The first movement switches the light on
- The next movement switches the light off
- The memory function restores the previous switching state after disconnection from the mains
- Sensor head K 59
- Sensor cable: 3 m
- Mains connection cable: 2 m, stripped and with Wire-end ferrules
- Switching cable: 0,3 m, stripped and with Wire-end ferrules
- For Connection to Screw- or Plug-in terminals
- For protection class II luminaire control gear
- For SlimLite® lines of light with up to 3 luminaires
- Distance between sensor and inside of door: 4 to 50 mm, depending on the surface
- Protection rating: IP20
- 220–240 V / 50–60 Hz
- Approaching the sensor triggers the switching operation
- Memory function after disconnection from the mains
- 3 m Sensor cable
- 2 m Mains connection cable, stripped and with Wire-end ferrules
- For switching LED Transformers up to 250 W
- 0,3 m Switching cable, stripped and with Wire-end ferrules

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	Gehäusefarbe
50612060112	IR-S with K 59 sensor AE	Anodized aluminum
50612060212	IR-S with K 60 sensor AE	Anodized aluminum
50612060312	IR-S with K 80 sensor AE	Anodized aluminum
50612060111	IR-S with K 59 sensor Euro	Anodized aluminum
50612060211	IR-S with K 60 sensor Euro	Anodized aluminum
50612060311	IR-S with K 80 sensor Euro	Anodized aluminum