

IN-Stick MF



7mm flat aluminium recessed luminaire LED IN-Stick MF 1130mm 20,4W ww



Description:

Lean recessed LED luminaire with homogeneous planar light for milled groove 20mm wide and 7mm deep, housing aluminum, supply cable 2.5m with LED 24 plug, colour appearance ww (warm white) approx. 3000K, optional accessories: dim controller with remote control, DALI or 1-10V

Connection: LED-Trafo DC 24V
Life: L70/B10 >= 50.000h
Light colour: 3000K warm white
Beam angle: 100°
Energy efficiency: LED 120 lm/W; luminaire: 1029 lm/m (55 lm/W)
Energy efficiency class: G
Colour rendering: Ra/CRI >= 95
Symbols: CE, MM, IP44, SK III
EAN-No.: 4,05E+12
Weight: 0,225 kg


Special features:

- only 7mm depth of the groove
- no visible luminous spots



IN-Stick MF

	100°	Ø	ww	nw
0,5m		560	1444 lx	1548 lx
1,0m		1120	361 lx	387 lx
1,5m		1680	160 lx	172 lx
2,0m		2240	90 lx	97 lx
2,5m		2800	58 lx	62 lx



Order number:
61002550402

limited availability



available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	light colour
61002550102	LED IN-Stick MF 330mm 5,8W ww	3000K warm white
61002550202	LED IN-Stick MF 530mm 9,6W ww	3000K warm white
61002550302	LED IN-Stick MF 830mm 15,1W ww	3000K warm white
61002550402	LED IN-Stick MF 1130mm 20,4W ww	3000K warm white
61002550103	LED IN-Stick MF 330mm 5,8W nw	4000K neutral white
61002550203	LED IN-Stick MF 530mm 9,6W nw	4000K neutral white
61002550303	LED IN-Stick MF 830mm 15,1W nw	4000K neutral white
61002550403	LED IN-Stick MF 1130mm 20,4W nw	4000K neutral white

