Twin-Stick 2

Pluggable linear luminaire 24V DC LED Twin-Stick 2 200mm 48 LED 3,0W cw






Description:
Pluggable LED Stick without dark zones in an aluminum profile, light color cool white approx. 5000K, easy installation with attached clips, simply connect the supply cable and connect the LED Sticks up to 2.4m or use one Stick SE (with lateral feeder) for infinite light rows, optional accessories: dimmable transformer with radio remote control or 1-10V dimmer, push-button switch, cover and milled profile for complete installation in wood

Connection: LED-Trafo DC 24 V
Life: L70/B10 >= 60.000 h
Light colour: 5000 K cool white
Beam angle: 55°
Energy efficiency: LED 98 lm/W; luminaire: 1140 lm/m (78 lm/W)
Energy efficiency class: G
Colour rendering: Ra/CRI >= 85
Symbols: CE, MM, UL, IP20, SK III
EAN-No.: 4051268010153
Weight: 0,045 kg

Special features:
- maximum 36 W or 2,4 m per supply cable
- without dark zones

Twin-Stick 2

55°	Ø	ww	nw	cw
0,5m	450	2600 lx	2820 lx	3120 lx
1,0m	900	650 lx	705 lx	780 lx
1,5m	1350	289 lx	313 lx	347 lx
2,0m	1800	163 lx	176 lx	195 lx
2,5m	2250	104 lx	113 lx	125 lx



Order number: 20202123201

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	light colour	colour rendering
20202123202	LED Twin-Stick 2 200mm 48 LED 3,0W ww	3000 K warm white	Ra/CRI >= 95
20202123302	LED Twin-Stick 2 300mm 72 LED 4,4W ww	3000 K warm white	Ra/CRI >= 95
20202123312	LED Twin-Stick 2 300mm 72 LED 4,4W ww SE 2,5m	3000 K warm white	Ra/CRI >= 95
20202123205	LED Twin-Stick 2 200mm 48 LED 3,0W nw	4000 K neutral white	Ra/CRI >= 95
20202123305	LED Twin-Stick 2 300mm 72 LED 4,4W nw	4000 K neutral white	Ra/CRI >= 95
20202123315	LED Twin-Stick 2 300mm 72 LED 4,4W nw SE 2,5m	4000 K neutral white	Ra/CRI >= 95
20202123201	LED Twin-Stick 2 200mm 48 LED 3,0W cw	5000 K cool white	Ra/CRI >= 85
20202123301	LED Twin-Stick 2 300mm 72 LED 4,4W cw	5000 K cool white	Ra/CRI >= 85
20202123311	LED Twin-Stick 2 300mm 72 LED 4,4W cw SE 2,5m	5000 K cool white	Ra/CRI >= 85

Order number: 20202123201