

## Basic-Tape S



Self-adhesive, silicone coated, ingress protection IP54 Set of 1 LED Basic-Tape S 900mm 8,1W xw + transformer 15W



### Description:


Flexible LED tape with silicon protection on roll, colour appearance extra warm white 2700 K, quick and easy installation due to 3M double-sided adhesive tape, supply cable 2,5 m already attached, the tape can be shortened at 50 mm (see marking). optional accessories: glass edge profile for lateral light supply of glass panes, corner profiles, cover profiles, milled profiles or mounting profiles, controller with radio remote control DALI, ZigBee or WiFi app

**Connection:** LED-Trafo DC 24 V  
**Life:** L70/B10 >= 40.000 h  
**Light colour:** 2700 K extra warm white  
**Beam angle:** 120°  
**Energy efficiency:** LED: 129 lm/W; luminaire: 780 lm/m (98 lm/W)  
**Energy efficiency class:** F  
**Colour rendering:** Ra/CRI >= 85  
**Symbols:** CE, MM, IP54, SK III  
**EAN-No.:** 4051268207379  
**Weight:** 0,238 kg

### Special features:

- max. 6 m per supply cable
- quick and easy installation due to double-sided adhesive tape
- tapes can be shortened at 50 mm intervals according to the marks on the front side)
- after removing the silicone layer from the connection pad the strips can be connected with the clips and connecting cables (now IP20 only)
- the power (W) of partial sections cannot be calculated linearly, please refer to the configurator!
- with IP54, suitable for applications requiring higher ingress protection (general humidity, bathroom, kitchen, shops). The silicone compound assures an additional mechanical protection e.g. for frequent cleaning work.

### Basic-Tape S

	120°	Ø	xw	ww	nw
0,5m		610	884 lx	952 lx	1024 lx
1,0m		1220	221 lx	238 lx	256 lx
1,5m		1830	98 lx	106 lx	114 lx
2,0m		2440	55 lx	60 lx	64 lx
2,5m		3050	35 lx	38 lx	41 lx



**Order number:**  
61059410104

limited availability

## available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	configurable	light colour
20202630234	LED Basic-Tape S 5m 600 LED 40W xw	Yes	2700 K extra warm white
20202630232	LED Basic-Tape S 5m 600 LED 40W ww	Yes	3000 K warm white
20202630233	LED Basic-Tape S 5m 600 LED 40W nw	Yes	4000 K neutral white
<b>61059410104</b>	<b>Set of 1 LED Basic-Tape S 900mm 8,1W xw + transformer 15W</b>	<b>No</b>	<b>2700 K extra warm white</b>
61059410114	Set of 1 LED Basic-Tape S 1000mm 9,0W xw + transformer 15W	No	2700 K extra warm white
61059410124	Set of 1 LED Basic-Tape S 1400mm 12,6W xw + transformer 15W	No	2700 K extra warm white
61059410134	Set of 1 LED Basic-Tape S 2400mm 21,1W xw + transformer 30W	No	2700 K extra warm white
61059410144	Set of 1 LED Basic-Tape S 2600mm 22,7W xw + transformer 30W	No	2700 K extra warm white
61059410154	Set of 1 LED Basic-Tape S 2800mm 24,4W xw + transformer 30W	No	2700 K extra warm white
61059410164	Set of 1 LED Basic-Tape S 3000mm 25,9W xw + transformer 30W	No	2700 K extra warm white
61059410174	Set of 1 LED Basic-Tape S 4600mm 37,5W xw + transformer 60W	No	2700 K extra warm white
61059410184	Set of 1 LED Basic-Tape S 5000mm 40,0W xw + transformer 60W	No	2700 K extra warm white
61059410112	Set of 1 LED Basic-Tape S 1000mm 9,0W ww + transformer 15W	No	3000 K warm white
61059410162	Set of 1 LED Basic-Tape S 3000mm 25,9W ww + transformer 30W	No	3000 K warm white
61059410113	Set of 1 LED Basic-Tape S 1000mm 9,0W nw + transformer 15W	No	4000 K neutral white
61059410163	Set of 1 LED Basic-Tape S 3000mm 25,9W nw + transformer 30W	No	4000 K neutral white

