

PS Mini

Milled filigree recessed power supply PS Mini adapter 0,1m anodized aluminium






Description:
power rail current collector with LED 24V connector

Connection: LED-Trafo DC 24 V
Symbols: CE, MM, IP20, SK III
EAN-No.: 4051268178877
Weight: 0,004 kg

Special features:

- invisible power supply, integrated into the system
- for flush-mounted installation
- both-sided power supply with a minimal material thickness of 38mm (2x 19mm)
- high variability because of stepless adjustment (without tools)
- colour: anodized aluminium, black and white on request
- PS Mini adapter holder for shelf bracket on request




Order number:
21545030102

article in stock


available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description
21802040026	Slotted rail PS Mini A 2000mm anodized aluminium + current carrying
21802040126	Slotted rail PS Mini B 2000mm anodized aluminium + current carrying
21802040006	Slotted rail PS Mini A 2000mm anodized aluminium
21802040116	Slotted rail PS Mini B 2000mm anodized aluminium
21304118002	PS Mini end cap anodized aluminium
21545012502	PS Mini feeder element anodized aluminium
21545030102	PS Mini adapter 0,1m anodized aluminium
21301010222	PS Mini adapter holder anodized aluminium




Slotted rail A




Slotted rail B


adapter holder



feeder element




end cap



adapter


Mounting variants

A




- for 19 mm
- rear screwed

B




- for 16 mm
- rear screwed



- for 19 mm
- flush with the adjacent areas
- rear screwed

A - B



- for 38 mm
- without screwing

Hera®

PS Mini

PS Mini adapter 0,1m anodized aluminium

Order number: 2154503102