

FQ 65 / 205



Dimmable recessed/surface mounted luminaire square FQ 65/205-LED 18W ww white



Description:

Dimmable recessed / surface mounted luminaire with planar light, plastic housing, incl. terminal for 230V with integrated through-wiring, colour appearance ww (warm white) approx. 3000K, quick and easy installation with adjustable mounting springs for all drill holes from 65 to 205mm, dimmable with phase dimmer

Connection: 220 - 240V / 50 - 60Hz
Life: L70/B10 >= 35.000h
Light colour: 3000K warm white
Beam angle: 115°
Energy efficiency: LED: 100 lm/W; luminaire: 1170 lm (65 lm/W)
Energy efficiency class: G
Colour rendering: Ra/CRI >= 80
Symbols: CE, MM, IP20, SK II
EAN-No.: 4,05E+12
Weight: 0,462 kg

Special features:

- Direct connection to 230V with integrated through-wiring
- no visible luminous spots
- adjustable mounting spring for all drill holes from 65 to 205mm
- recommended phase dimmer: Busch-Jaeger 6523U-102, Jung 1730DD or Sygonix 33594R


FR- / FQ 65/205

	115°	Ø	xw	ww	nw
0,5m		650	1580 lx	1660 lx	1744 lx
1,0m		1300	395 lx	415 lx	436 lx
1,5m		1950	176 lx	184 lx	194 lx
2,0m		2600	99 lx	104 lx	109 lx
2,5m		3250	63 lx	66 lx	70 lx

Drilling hole



65-205mm



Order number:
20203080102

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	light colour
20203080103	FQ 65/205-LED 18W xw white	2700K extra warm white
20203080102	FQ 65/205-LED 18W ww white	3000K warm white
20203080101	FQ 65/205-LED 18W nw white	4000K neutral white

