

R 68 HO

Flat recessed luminaire round R 68-LED HO 4W ww stainless steel



Description:

LED recessed spotlight, plastic housing, connecting cable 2.5m with LED 24-plug, light color warm white approx. 3000K, quick and easy installation with snap-in hooks, optional accessories: dimmable transformer with radio remote control or 1-10V dimmer, mounting spring for a safe hold in lightweight ceilings, surface mounting ring for installation without mounting hole

Connection: LED-Trafo DC 24V
Life: L70/B10 >= 40.000h
Light colour: 3000K warm white
Beam angle: 110°
Energy efficiency: LED: 113 lm/W; luminaire: 300 lm (75 lm/W)
Energy efficiency class: G
Colour rendering: Ra/CRI >= 93
Symbols: CE, MM, UL, IP44, SK III
EAN-No.: 4,05E+12
Weight: 0,08 kg

Special features:

- flush mounting in 16mm panels


R 68 HO / Q 68 HO

	110°	Ø	ww	nw
0,5m		620	532 lx	532 lx
1,0m		1240	133 lx	133 lx
1,5m		1860	59 lx	59 lx
2,0m		2480	33 lx	33 lx
2,5m		3100	21 lx	21 lx

Drilling hole



68mm



Order number:
61001261208

limited availability

available versions

Choose from the options below. The currently selected one is highlighted in color.

article number	description	colour of housing
61001261206	R 68-LED HO 4W ww matt chrome	Matt chrome
61001261208	R 68-LED HO 4W ww stainless steel	Stainless steel

