Power-Stick S

Powerful, pluggable linear luminaire 24V DC LED Power-Stick S 200mm 6 LED 2,7W xw






Descripción:
Plug-in LED stick without dark zones in aluminium profile, colour appearance `xw` approx.2700K, easy mounting by enclosed clips, supply cable easy to attach and up to 2,4m of sticks or one stick SE (with side-connection) for continuous strip lighting, optional accessory: dimmable transformer with radio telecontrol or 1-10V Dimmer, push switch, cover and milled profile for complete recessing in wood

Conexión:	220 - 240V / 50 - 60Hz
Vida útil:	L70/B10 >= 40.000 h
Lichtfarbe:	2700 K blanco extra cálido
Ausstrahlungswinkel:	120°
Eficiencia energética:	LED 113 lm/W; luminaire: 935 lm/m (70 lm/W)
Energieeffizienzklasse:	G
Reproducción de colores:	Ra/CRI >= 95
Zeichen:	CE, MM, IP20, SK III
EAN-Nr.:	4051268108027
Gewicht:	0,025 kg


Particularidades:

- max. 32 W or 2,4 m per supply cable
- without dark zones
- LED Stick with lateral feeder for continuous strip lighting

Power-Stick S



	Ø	xw	ww	nw
0,5m	610	1660 lx	1700 lx	1800 lx
1,0m	1220	415 lx	425 lx	450 lx
1,5m	1830	184 lx	189 lx	200 lx
2,0m	2440	104 lx	106 lx	113 lx
2,5m	3050	66 lx	68 lx	72 lx



N.° de artículo:
20202410104

artículo disponible en stock

Versiones disponibles

Elija uno de los siguientes modelos. El seleccionado actualmente está resaltado.

N.° de artículo	Denominación	Color de la luz
20202410104	LED Power-Stick S 200mm 6 LED 2,7W xw	2700 K blanco extra cálido
20202410204	LED Power-Stick S 300mm 12 LED 4,0W xw	2700 K blanco extra cálido
20202411204	LED Power-Stick S 300mm 12 LED 4,0W xw SE 2,5m	2700 K blanco extra cálido
20202410102	LED Power-Stick S 200mm 6 LED 2,7W ww	3000 K blanco cálido
20202410202	LED Power-Stick S 300mm 12 LED 4,0W ww	3000 K blanco cálido
20202411202	LED Power-Stick S 300mm 12 LED 4,0W ww SE 2,5m	3000 K blanco cálido
20202410103	LED Power-Stick S 200mm 6 LED 2,7W nw	4000 K blanco neutro
20202410203	LED Power-Stick S 300mm 12 LED 4,0W nw	4000 K blanco neutro
20202411203	LED Power-Stick S 300mm 12 LED 4,0W nw SE 2,5m	4000 K blanco neutro

N.º de artículo: 20202410104

