IN-Stick HR

Powerful aluminium recessed luminaire with reflector LED IN-Stick HR 330mm 7,5W ww






Descripción:
Flat recessed LED luminaire with homogeneous planar light for milling groove 20mm wide and 12mm deep, housing aluminum, supply cable 2.5m with LED 24 plug, colour appearance ww (warm white) approx. 3000K, optional accessories: dim controller with remote control, DALI or 1-10V


Conexión:	LED-Trafo DC 24 V
Vida útil:	L70/B10 >= 60.000 h
Lichtfarbe:	3000 K blanco cálido
Ausstrahlungswinkel:	100°
Eficiencia energética:	LED 113 lm/W; luminaire: 1342 lm/m (54 lm/W)
Energieeffizienzklasse:	G
Reproducción de colores:	Ra/CRI >= 95
Zeichen:	CE, MM, IP44, SK III
EAN-Nr.:	4051268113571
Gewicht:	0,145 kg

Particularidades:
- only 12 mm depth of the groove
- version HR with reflector for asymmetrical illumination

IN-Stick HR



	Ø	ww	nw
0,5m	560	2640 lx	2720 lx
1,0m	1120	660 lx	680 lx
1,5m	1680	293 lx	302 lx
2,0m	2240	165 lx	170 lx
2,5m	2800	106 lx	109 lx



N.° de artículo:
61001412102

disponibilidad restringida probable

Versiones disponibles

Elija uno de los siguientes modelos. El seleccionado actualmente está resaltado.

N.° de artículo	Denominación	Color de la luz
61001412102	LED IN-Stick HR 330mm 7,5W ww	3000 K blanco cálido
61001412202	LED IN-Stick HR 530mm 12,5W ww	3000 K blanco cálido
61001412302	LED IN-Stick HR 830mm 20,0W ww	3000 K blanco cálido
61001412402	LED IN-Stick HR 1130mm 27,5W ww	3000 K blanco cálido
61001412101	LED IN-Stick HR 330mm 7,5W nw	4000 K blanco neutro
61001412201	LED IN-Stick HR 530mm 12,5W nw	4000 K blanco neutro
61001412301	LED IN-Stick HR 830mm 20,0W nw	4000 K blanco neutro
61001412401	LED IN-Stick HR 1130mm 27,5W nw	4000 K blanco neutro

N.º de artículo: 61001412102