

SR 68



Swivel and tilt recessed ceiling spotlight for 68-80mm ceiling cut-out SR 68-LED 4,8W 35° xw white



Descripción:

Swiveling LED recessed spotlight, metal housing, connecting cable 0.2m with LED 350 plug, quick and easy installation by spring clips, optional accessories: dimmable transformer for phase dimmer or 1-10V dimmer, light color extra warm white approx. 2700K, gimbal swivel around each 20°

Conexión: LED-Trafo DC 350mA
Vida útil: L70/B10 >= 70.000h
Lichtfarbe: 2700K blanco extra cálido
Ausstrahlungswinkel: 35°
Eficiencia energética: LED: 120 lm/W luminaire 485 lm (100 lm/W incl. transformer)
Energieeffizienzklasse: E
Reproducción de colores: Ra/CRI >= 90
Zeichen: CE, MM, UL, IP44, UGR<19, SK III
EAN-Nr.: 4,05E+12
Gewicht: 0,11 kg

Particularidades:

- swivels and tilts 20° to both sides
- metal casing
- suitable for screen workplaces! (UGR < 19)


SR 68 4,8W

35°	Ø	xw	ww	nw
0,5m	280	3650 lx	3880 lx	4216 lx
1,0m	560	912 lx	970 lx	1054 lx
1,5m	840	406 lx	431 lx	468 lx
2,0m	1120	228 lx	243 lx	264 lx
2,5m	1400	146 lx	155 lx	169 lx

Agujero



68-74mm (ohne Ring)
 68-84mm (mit Ring)



N.º de artículo:
 20202401701

artículo disponible en stock

Versiones disponibles

Elija uno de los siguientes modelos. El seleccionado actualmente está resaltado.

N.º de artículo	Denominación	Color de la carcasa	Ángulo del haz	Color de la luz
20202401401	SR 68-LED 4,8W 35° xw matt chrome	Cromo mate	35°	2700K blanco extra cálido
20202402001	SR 68-LED 4,8W 35° xw stainless steel look	Aspecto acero inoxidable	35°	2700K blanco extra cálido
20202401701	SR 68-LED 4,8W 35° xw white	Blanco	35°	2700K blanco extra cálido
20202400201	SR 68-LED 4,8W 22° ww matt chrome	Cromo mate	22°	3000K blanco cálido
20202401201	SR 68-LED 4,8W 35° ww matt chrome	Cromo mate	35°	3000K blanco cálido
20202401801	SR 68-LED 4,8W 35° ww stainless steel look	Aspecto acero inoxidable	35°	3000K blanco cálido
20202401501	SR 68-LED 4,8W 35° ww white	Blanco	35°	3000K blanco cálido
20202400301	SR 68-LED 4,8W 22° nw matt chrome	Cromo mate	22°	4000K blanco neutro
20202401301	SR 68-LED 4,8W 35° nw matt chrome	Cromo mate	35°	4000K blanco neutro
20202401901	SR 68-LED 4,8W 35° nw stainless steel look	Aspecto acero inoxidable	35°	4000K blanco neutro
20202401601	SR 68-LED 4,8W 35° nw white	Blanco	35°	4000K blanco neutro
20202401001	SR 68-LED 4,8W 35° xw black	Negro	35°	2700K blanco extra cálido
20202400801	SR 68-LED 4,8W 35° ww black	Negro	35°	3000K blanco cálido

