

LED-2-Link Spot



Rotate and swivel aluminium showcase spotlight LED 2 Link Spot 1x 1,5W ww black



Descripción:

rotate and swivel LED Spot, combinable, metal housing, light appearance warm white approx. 3000K, feed-through wiring with LED 24 plug + LED 24 connector, optional accessories: various recessed and surface-mounted profiles as well as combinable with different kinds of luminaires, Dim-Controller with remote control, 1-10V, DALI, ZigBee, Sonar or WiFi


Conexión: LED-Trafo DC 24V
Vida útil: L90/B10 >= 60.000h
Lichtfarbe: 3000K blanco cálido
Ausstrahlungswinkel: 38°
Eficiencia energética: LED 110 lm/W; luminaire: 80 lm (53 lm/W)
Energieeffizienzklasse: G
Reproducción de colores: Ra/CRI >= 90
Zeichen: CE, MM, UL, IP20, SK III
EAN-Nr.: 4,05E+12
Gewicht: 0,038 kg

Particularidades:

- 300° rotatable and swivelable by 300°
- max. 48W per supply cable
- dimmable (only 1 controller per transformer)

LED-2-Link Spot

	38°	Ø	ww	nw
0,5m		290	424 lx	520 lx
1,0m		580	106 lx	130 lx
1,5m		870	47 lx	58 lx
2,0m		1160	27 lx	33 lx
2,5m		1450	17 lx	21 lx




N.º de artículo:
61002130302

artículo disponible en stock

Versiones disponibles

Elija uno de los siguientes modelos. El seleccionado actualmente está resaltado.

N.º de artículo	Denominación	Color de la carcasa	Color de la luz
61002130302	LED 2 Link Spot 1x 1,5W ww black	Negro	3000K blanco cálido
61002130102	LED 2 Link Spot 1x 1,5W ww anodized aluminium	Aluminio anodizado	3000K blanco cálido
61002130303	LED 2 Link Spot 1x 1,5W nw black	Negro	4000K blanco neutro
61002130103	LED 2 Link Spot 1x 1,5W nw anodized aluminium	Aluminio anodizado	4000K blanco neutro
61002133302	LED 2 Link Spot 3x 1,5W ww black	Negro	3000K blanco cálido
61002133102	LED 2 Link Spot 3x 1,5W ww anodized aluminium	Aluminio anodizado	3000K blanco cálido
61002133303	LED 2 Link Spot 3x 1,5W nw black	Negro	4000K blanco neutro
61002133103	LED 2 Link Spot 3x 1,5W nw anodized aluminium	Aluminio anodizado	4000K blanco neutro



LED 24

