

Accessories Dynamic/RGB luminaires



Light control (from extra warm 2700K to cold white 5000K) UP Wireless push-button module Smart System




Descripción:

Flush-mounted wireless push-button module as an extension for teaching existing Smart System wireless controllers, with memory function (the previous status is restored after disconnection from the mains), for direct 230V connection to a push-button provided by the customer

Zeichen: CE, MM, IP20

EAN-Nr.: 4,05E+12

Gewicht: 0,017 kg



N.º de artículo:
20805002052

disponibilidad restringida probable

Versiones disponibles

Elija uno de los siguientes modelos. El seleccionado actualmente está resaltado.

N.º de artículo	Denominación	Sistema de enchufe	Clase de protección
21535061001	Connecting cable Dynamic 1m	Dynamic	SK3
21535062501	Connecting cable Dynamic 2,5m	Dynamic	SK3
21508060714	Dynamic 4-way distributor	Dynamic	SK3
21542062501	RGB connecting cable 2,5m	RGB	SK3
21508060705	LED RGB 4-way distributor	RGB	SK3
21535012501	Supply cable Dynamic Tape 2,5m	Dynamic	SK3
21534062511	Supply cable Dynamic Tape 2,5m	Dynamic	SK3
21535000201	Corner clip Dynamic Tape	Dynamic	SK3
21535000101	Connecting clip Dynamic Tape	Dynamic	SK3
21535060001	Connecting cable Dynamic Tape 50mm	Dynamic	SK3
20805002052	UP Wireless push-button module Smart System	LED 24	-
61500050633	4-channel Smart System wireless remote control	LED 24	SK3
61500050673	3-channel H-iDrive wireless remote control Smart System	LED 24	SK3
61500050646	Smart System surface-mounted wireless remote control	LED 24	SK3

