

R 68 HO

Flat recessed luminaire round R 68-LED HO 4W ww stainless steel



Descripción:

LED recessed spotlight, plastic housing, connecting cable 2.5m with LED 24-plug, light color warm white approx. 3000K, quick and easy installation with snap-in hooks, optional accessories: dimmable transformer with radio remote control or 1-10V dimmer, mounting spring for a safe hold in lightweight ceilings, surface mounting ring for installation without mounting hole


Conexión: LED-Trafo DC 24V
Vida útil: L70/B10 >= 40.000h
Lichtfarbe: 3000K blanco cálido
Ausstrahlungswinkel: 110°
Eficiencia energética: LED: 113 lm/W; luminaire: 300 lm (75 lm/W)
Energieeffizienzklasse: G
Reproducción de colores: Ra/CRI >= 93
Zeichen: CE, MM, UL, IP44, SK III
EAN-Nr.: 4,05E+12
Gewicht: 0,08 kg

Particularidades:

- flush mounting in 16mm panels

R 68 HO / Q 68 HO


	110°	Ø	ww	nw
0,5m		620	532 lx	532 lx
1,0m		1240	133 lx	133 lx
1,5m		1860	59 lx	59 lx
2,0m		2480	33 lx	33 lx
2,5m		3100	21 lx	21 lx



Agujero



68mm



N.º de artículo:
61001261208

disponibilidad restringida probable

Versiones disponibles

Elija uno de los siguientes modelos. El seleccionado actualmente está resaltado.

N.º de artículo	Denominación	Color de la carcasa
61001261206	R 68-LED HO 4W ww matt chrome	Cromo mate
61001261208	R 68-LED HO 4W ww stainless steel	Aspecto acero inoxidable

