

IN-Stick H



Foco empotrado de aluminio potente LED IN-Stick H 830mm 20,0W nw



Descripción:

Flat recessed LED luminaire with homogeneous planar light for milled groove 20mm wide and 12mm deep, housing aluminum, supply cable 2.5m with LED 24 plug, colour appearance nw (neutral white) approx. 4000K, optional accessories: dim controller with remote control, DALI or 1-10V

Conexión: LED-Trafo DC 24V
Vida útil: L70/B10 >= 60.000h
Lichtfarbe: 4000K blanco neutro
Ausstrahlungswinkel: 100°
Eficiencia energética: LED 113 lm/W; Luminaria: 1342 lm/m (54 lm/W)


Energieeffizienzklasse: G
Reproducción de colores: Ra/CRI >= 95
Zeichen: CE, MM, IP44, SK III
EAN-Nr.: 4,05E+12
Gewicht: 0,33 kg

Particularidades:

- solo 12mm de profundidad de fresado
- versión HR con reflector para iluminación asimétrica

IN-Stick H

	100°	Ø	ww	nw
0,5m		560	2640 lx	2720 lx
1,0m		1120	660 lx	680 lx
1,5m		1680	293 lx	302 lx
2,0m		2240	165 lx	170 lx
2,5m		2800	106 lx	109 lx



N.º de artículo:
61001410301

disponibilidad restringida probable

Versiones disponibles

Elija uno de los siguientes modelos. El seleccionado actualmente está resaltado.

N.º de artículo	Denominación	Color de la luz
61001410102	LED IN-Stick H 330mm 7,5W ww	3000K blanco cálido
61001410202	LED IN-Stick H 530mm 12,5W ww	3000K blanco cálido
61001410302	LED IN-Stick H 830mm 20,0W ww	3000K blanco cálido
61001410402	LED IN-Stick H 1130mm 27,5W ww	3000K blanco cálido
61001410101	LED IN-Stick H 330mm 7,5W nw	4000K blanco neutro
61001410201	LED IN-Stick H 530mm 12,5W nw	4000K blanco neutro
61001410301	LED IN-Stick H 830mm 20,0W nw	4000K blanco neutro
61001410401	LED IN-Stick H 1130mm 27,5W nw	4000K blanco neutro

