Top-Stick H

Powerful aluminium surface mounted luminaire LED Top-Stick H 1210mm 30,0W nw





Descripción:
Flat LED under-cabinet luminaire, housing anodized aluminium, supply cable 2,5 m with LED 24 plug, colour appearance neutral white appr.4000K, accessories available: dimmable transformer with radio telecontrol or 1-10V Dimmer


Conexión:	LED-Trafo DC 24 V
Vida útil:	L70/B10 >= 60.000 h
Lichtfarbe:	4000 K blanco neutro
Ausstrahlungswinkel:	100°
Eficiencia energética:	LED 113 lm/W; luminaire: 1302 lm/m (52 lm/W)
Energieeffizienzklasse:	G
Reproducción de colores:	Ra/CRI >= 95
Zeichen:	CE, MM, IP20, SK III
EAN-Nr.:	4051268108713
Gewicht:	0,56 kg

Particularidades:

- only 12 mm thickness
- easy mounting with concealed mounting clips
- version HR with reflector for asymmetrical illumination

Top-Stick H

100°	Ø	ww	nw
0,5m	610	2580 lx	2680 lx
1,0m	1220	645 lx	670 lx
1,5m	1830	287 lx	298 lx
2,0m	2440	161 lx	168 lx
2,5m	3050	103 lx	107 lx



N.º de artículo:
61001420401

disponibilidad restringida probable

Versiones disponibles

Elija uno de los siguientes modelos. El seleccionado actualmente está resaltado.

N.º de artículo	Denominación	Color de la luz
61001420102	LED Top-Stick H 310mm 7,5W ww	3000 K blanco cálido
61001420202	LED Top-Stick H 610mm 15,0W ww	3000 K blanco cálido
61001420302	LED Top-Stick H 910mm 22,5W ww	3000 K blanco cálido
61001420402	LED Top-Stick H 1210mm 30,0W ww	3000 K blanco cálido
61001420101	LED Top-Stick H 310mm 7,5W nw	4000 K blanco neutro
61001420201	LED Top-Stick H 610mm 15,0W nw	4000 K blanco neutro
61001420301	LED Top-Stick H 910mm 22,5W nw	4000 K blanco neutro
61001420401	LED Top-Stick H 1210mm 30,0W nw	4000 K blanco neutro

N.º de artículo: 61001420401

