

IN-Stick H



Faretto incassato in alluminio potente LED IN-Stick H 330mm 7,5W ww



Descrizione:

Flat recessed LED luminaire with homogeneous planar light for milled groove 20mm wide and 12mm deep, housing aluminum, supply cable 2.5m with LED 24 plug, colour appearance ww (warm white) approx. 3000K, optional accessories: dim controller with remote control, DALI or 1-10V

Collegamento: LED-Trafo DC 24V
Durata: L70/B10 >= 60.000h
Lichtfarbe: 3000K bianco caldo
Ausstrahlungswinkel: 100°
Efficienza energetica: LED 113 lm/W; Apparecchio: 1342 lm/m (54 lm/W)


Energieeffizienzklasse: G
Resa del colore: Ra/CRI >= 95
Zeichen: CE, MM, IP44, SK III
EAN-Nr.: 4,05E+12
Gewicht: 0,145 kg

Particolarità:

- o solo 12mm di profondità di fresatura
- o versione HR con riflettore per illuminazione asimmetrica

IN-Stick H

	100°	Ø	ww	nw
0,5m		560	2640 lx	2720 lx
1,0m		1120	660 lx	680 lx
1,5m		1680	293 lx	302 lx
2,0m		2240	165 lx	170 lx
2,5m		2800	106 lx	109 lx





N. articolo:
61001410102

eventualmente disponibili in quantità limitata


Versioni disponibili

Scegli tra le versioni seguenti. Quella attualmente selezionata è evidenziata a colori.


N. articolo	Denominazione	Colore della luce
61001410102	LED IN-Stick H 330mm 7,5W ww	3000K bianco caldo
61001410202	LED IN-Stick H 530mm 12,5W ww	3000K bianco caldo
61001410302	LED IN-Stick H 830mm 20,0W ww	3000K bianco caldo
61001410402	LED IN-Stick H 1130mm 27,5W ww	3000K bianco caldo
61001410101	LED IN-Stick H 330mm 7,5W nw	4000K bianco neutro
61001410201	LED IN-Stick H 530mm 12,5W nw	4000K bianco neutro
61001410301	LED IN-Stick H 830mm 20,0W nw	4000K bianco neutro
61001410401	LED IN-Stick H 1130mm 27,5W nw	4000K bianco neutro



LED IN-Stick H



LED IN-Stick HR



60°
20°