
Dynamic FR- / FQ 68/78

Flat recessed luminaire round with adjustable colour appearance Dynamic FR 68-LED 4W black






Descrizione:
LED recessed spotlight with planar light, plastic housing, connecting cable 2.5m with dynamic plug, light color adjustable between approx. 2700K and 5000K, quick and easy installation with snap-in hooks, optional accessories: mounting spring for a secure hold in lightweight ceilings, surface-mounting ring for installation without mounting hole, control via radio remote control or WiFi controller

Collegamento: LED-Trafo DC 24 V
Durata: L70/B10 >= 50.000 h
Lichtfarbe: 2700 – 5000 K (Dynamic) regolabile
Ausstrahlungswinkel: 110°
Efficienza energetica: LED: 113 lm/W; luminaire: 270 lm (68 lm/W)
Energieeffizienzklasse: G
Resa del colore: Ra/CRI >= 93
Zeichen: CE, MM, UL, IP44, SK III
EAN-Nr.: 4051268176811
Gewicht: 0,07 kg

Particolarità:
- flush mounting in 16 mm panels
- no visible luminous spots
- light colour adjustable between approx. 2700 K (xw) and 5000 K (cw)

Dynamic FR-/FQ 68-LED




	Ø	ww	nw	cw
0,5m	620	372 lx	400 lx	444 lx
1,0m	1240	93 lx	100 lx	111 lx
1,5m	1860	41 lx	44 lx	49 lx
2,0m	2480	23 lx	25 lx	28 lx
2,5m	3100	15 lx	16 lx	18 lx

Perforazione



68mm



N. articolo:
61001600103

Articoli in stock

Versioni disponibili


Scegli tra le versioni seguenti. Quella attualmente selezionata è evidenziata a colori.


N. articolo	Denominazione	Colore esterno
61001600103	Dynamic FR 68-LED 4W black	nero
61001600106	Dynamic FR 68-LED 4W matt chrome	cromato opaco
61001600108	Dynamic FR 68-LED 4W stainless steel	aspetto in acciaio inossidabile
61057230108	set of 3 Dynamic FR 68-LED 4W stainless steel	aspetto in acciaio inossidabile


Hera®

Dynamic FR- / FQ 68/78
Dynamic FR 68-LED 4W black

N. articolo: 61001600103







Dynamic FR 68-LED

Dynamic FQ 68-LED

Dynamic FR 78-LED

