# Eco HV SR 68

Swivel and tilt 230V recessed ceiling spotlight with switchable colour appearance  Eco HV SR 68-LED 5W ww/nw white






**Descrizione:**
Swiveling LED recessed spotlight, incl. connecting terminal for 230V with integrated through-wiring, quick and easy installation by spring terminals, light color ww (warm white) approx. 3000K, or nw (neutral white) approx. 4000K for setting at the spotlight housing, swiveling by 20 ° each

| | |
|---|---|
| **Collegamento:** | 220 - 240V / 50 - 60Hz |
| **Durata:** | L70/B10 >= 40.000 h |
| **Lichtfarbe:** | 3000 / 4000 K commutabile |
| **Ausstrahlungswinkel:** | 38° |
| **Efficienza energetica:** | LED: 129 lm/W; luminaire: 400 / 425 lm (80 / 85 lm/W) |
| **Energieeffizienzklasse:** | F |
| **Resa del colore:** | Ra/CRI >= 80 |
| **Zeichen:** | CE, MM, IP20, SK II |
| **EAN-Nr.:** | 4051268188593 |
| **Gewicht:** | 0,114 kg |

**Particolarità:**

- for direct change of the two light colours at the spotlight housing
- direct connection to 230 V with integrated through-wiring
- swiveling radius 20°
- not dimmable

Eco HV SR 68





| 38° | Ø | ww | nw |
|---|---|---|---|
| 0,5m | 290 | 2400 lx | 2528 lx |
| 1,0m | 580 | 600 lx | 632 lx |
| 1,5m | 870 | 267 lx | 281 lx |
| 2,0m | 1160 | 150 lx | 158 lx |
| 2,5m | 1450 | 96 lx | 101 lx |

Perforazione



68mm




**N. articolo:**
20202941001

eventualmente disponibili in quantità limitata

## Versioni disponibili

Scegli tra le versioni seguenti. Quella attualmente selezionata è evidenziata a colori.

| N. articolo | Denominazione | Colore esterno |
|---|---|---|
| 20202941001 | Eco HV SR 68-LED 5W ww/nw white | bianco |
| 20202946001 | Eco HV SR 68-LED 5W ww/nw matt chrome | cromato opaco |

N. articolo: 20202941001

