# FR/FQ 65/205

Dimmable recessed/surface mounted luminaire square  FQ 65/205-LED 18W xw white






**Descrizione:**
Dimmable recessed / surface mounted luminaire with planar light, plastic housing, incl. terminal for 230V with integrated through-wiring, colour appearance xw (extra warm white) approx. 2700K, quick and easy installation with adjustable mounting springs for all drill holes from 65 to 205 mm, dimmable with phase dimmer

**Collegamento:** 220 - 240V / 50 - 60Hz
**Durata:** L70/B10 >= 35.000 h
**Lichtfarbe:** 2700 K bianco extra caldo
**Ausstrahlungswinkel:** 115°
**Efficienza energetica:** LED: 100 lm/W; luminaire: 1170 lm (65 lm/W)
**Energieeffizienzklasse:** G
**Resa del colore:** Ra/CRI >= 80
**Zeichen:** CE, MM, IP20, SK II
**EAN-Nr.:** 4051268198998
**Gewicht:** 0,462 kg

**Particolarità:**

- Direct connection to 230V with integrated through-wiring
- no visible luminous spots
- adjustable mounting spring for all drill holes from 65 to 205mm
- recommended phase dimmer: Busch-Jaeger 6523U-102, Jung 1730DD or Sygonix 33594R

FR- / FQ 65/205





| | Ø | xw | ww | nw |
|---|---|---|---|---|
| 0,5m | 650 | 1580 lx | 1660 lx | 1744 lx |
| 1,0m | 1300 | 395 lx | 415 lx | 436 lx |
| 1,5m | 1950 | 176 lx | 184 lx | 194 lx |
| 2,0m | 2600 | 99 lx | 104 lx | 109 lx |
| 2,5m | 3250 | 63 lx | 66 lx | 70 lx |

Perforazione



65-205mm





**N. articolo:**
20203080103

eventualmente disponibili in quantità limitata

## Versioni disponibili

Scegli tra le versioni seguenti. Quella attualmente selezionata è evidenziata a colori.

| N. articolo | Denominazione | Colore della luce |
|---|---|---|
| 20203080103 | FQ 65/205-LED 18W xw white | 2700 K bianco extra caldo |
| 20203080102 | FQ 65/205-LED 18W ww white | 3000 K bianco caldo |
| 20203080101 | FQ 65/205-LED 18W nw white | 4000 K bianco neutro |

N. articolo: 20203080103

