

ECO R 68



Recessed ceiling spotlight with switchable power/light colour Eco R 68 module 5/8W xw/ww/nw/xc



Descrizione:

Dimmable recessed LED spotlight, incl. connection terminal for 230V with integrated through-wiring, quick and easy installation thanks to mounting spring, light color and power switchable on the spotlight

Collegamento: 220 - 240V / 50 - 60Hz
Durata: L70/B10 >= 50.000h
Lichtfarbe: 3000 / 4000K commutabile
Ausstrahlungswinkel: 60°
Effizienz energetica: luminaire: 565 / 880 lm (116 / 111 lm/W)
Energieeffizienzklasse: F
Resa del colore: Ra/CRI >= 80
Zeichen: CE, MM, VDE-GS, IP65, SK II
EAN-Nr.: 4,05E+12
Gewicht: 0,22 kg

Particolarità:

- two power levels switchable on the spotlight (5/8W)
- four colour appearances switchable on the spotlight (xw/ww/nw/xc)
- direct connection to 230V with integrated through-wiring or Wieland/Adels plug
- thanks to IP65 ideally suited for applications with increased protection rating (general moisture, e.g. bathroom and kitchen areas)
- recommended phase dimmer: Busch-Jaeger 6523U-102, Jung 266GDE or GIRA 117600/I03
- please order decorative ring in white, black, polished chrome or stainless steel look separately


Eco R 68 8W

60°	Ø	xw	ww	nw	xc
0,5m	340	3844 lx	4140 lx	4352 lx	4056 lx
1,0m	680	961 lx	1035 lx	1088 lx	1014 lx
1,5m	1020	427 lx	460 lx	484 lx	451 lx
2,0m	1360	240 lx	259 lx	272 lx	254 lx
2,5m	1700	154 lx	166 lx	174 lx	162 lx

Perforazione



68-80 mm



N. articolo:
20807081001

Articoli in stock

Versioni disponibili

Scegli tra le versioni seguenti. Quella attualmente selezionata è evidenziata a colori.

N. articolo	Denominazione
20807081001	Eco R 68 module 5/8W xw/ww/nw/xc

