

R 68 HO



Flat recessed luminaire round R 68-LED HO 4W ww stainless steel



Descrizione:

LED recessed spotlight, plastic housing, connecting cable 2.5m with LED 24-plug, light color warm white approx. 3000K, quick and easy installation with snap-in hooks, optional accessories: dimmable transformer with radio remote control or 1-10V dimmer, mounting spring for a safe hold in lightweight ceilings, surface mounting ring for installation without mounting hole


Collegamento: LED-Trafo DC 24V
Durata: L70/B10 >= 40.000h
Lichtfarbe: 3000K bianco caldo
Ausstrahlungswinkel: 110°
Efficienza energetica: LED: 113 lm/W; luminaire: 300 lm (75 lm/W)
Energieeffizienzklasse: G
Resa del colore: Ra/CRI >= 93
Zeichen: CE, MM, UL, IP44, SK III
EAN-Nr.: 4,05E+12
Gewicht: 0,08 kg

Particolarità:

- flush mounting in 16mm panels

R 68 HO / Q 68 HO


	110°	Ø	ww	nw
0,5m		620	532 lx	532 lx
1,0m		1240	133 lx	133 lx
1,5m		1860	59 lx	59 lx
2,0m		2480	33 lx	33 lx
2,5m		3100	21 lx	21 lx



Perforazione



68mm



N. articolo:
61001261208

eventualmente disponibili in quantità limitata

Versioni disponibili

Scegli tra le versioni seguenti. Quella attualmente selezionata è evidenziata a colori.

N. articolo	Denominazione	Colore esterno
61001261206	R 68-LED HO 4W ww matt chrome	Cromato opaco
61001261208	R 68-LED HO 4W ww stainless steel	Aspetto in acciaio inossidabile

