

SIL-LED 2



Compact furniture drawer luminair with IR sensor SIL-LED 2 461mm 1,7W nw



Descrizione:

Interior cabinet luminaire with touchless sensor switch, supply cable 2.5m with LED 24 plug, colour appearance nw (neutral white) approx. 4000K, incl. mounting clip for lateral attachment in drawers and 500mm self-adhesive cable duct


Collegamento: LED-Trafo DC 24V
Durata: L70/B10 >= 50.000h
Lichtfarbe: 4000K bianco neutro
Ausstrahlungswinkel: 110°
Efficienza energetica: LED: 140 lm/W; lampada: 330 lm/m (83 lm/W)
Energieeffizienzklasse: G
Resa del colore: Ra/CRI >= 80
Zeichen: CE, MM, IP20, SK III
EAN-Nr.: 4,05E+12
Gewicht: 0,25 kg

Particolarità:

- interruttore a sensore senza contatto integrato, con "Soft On" e "Soft Off"
- clip di montaggio in allegato per il fissaggio laterale nei cassetti

SIL-LED 2

	110°	Ø	567mm
0,5m		610	268 lx
1,0m		1220	67 lx
1,5m		1830	30 lx
2,0m		2440	17 lx
2,5m		3050	11 lx



N. articolo:
61001214201

eventualmente disponibili in quantità limitata

Versioni disponibili

Scegli tra le versioni seguenti. Quella attualmente selezionata è evidenziata a colori.

N. articolo	Denominazione
61001213101	SIL-LED 2 417mm 1,3W nw
61001213201	SIL-LED 2 467mm 1,7W nw
61001213301	SIL-LED 2 567mm 2,1W nw
61001213401	SIL-LED 2 767mm 2,9W nw
61001213501	SIL-LED 2 867mm 3,4W nw
61001213601	SIL-LED 2 967mm 3,8W nw
61001213701	SIL-LED 2 1167mm 4,7W nw
61001214101	SIL-LED 2 411mm 1,3W nw
61001214201	SIL-LED 2 461mm 1,7W nw
61001214301	SIL-LED 2 561mm 2,1W nw
61001214401	SIL-LED 2 761mm 2,9W nw
61001214501	SIL-LED 2 861mm 3,4W nw
61001214601	SIL-LED 2 961mm 3,8W nw
61001214701	SIL-LED 2 1161mm 4,7W nw

